ProLite E2710HDSD-1

The New Prolite E2710HDSD 27” LCD Display features a stunning 2 ms Response Time and a High Definition 1920x 1080 Resolution. The 20,000:1 Advanced Contrast Ratio and 400 cd/m² brightness offer the user clear and vivid images, and the DVI, D-Sub and USB connections ensure compatibility across a range of devices including games consoles and work stations. The display is Windows® 7 Compatible and Energy Star 5.0 qualified.

Panel	TN
Diagonal	27"
Display area h x w	336.2 x 597.6 mm; 13.2" x 23.5"
Response time	2 ms
Contrast	20 000 : 1 ACR
Contrast	1000 : 1 typical
Brightness	400 cd/m² typical
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°
Display colour	16.7 million
Pixel pitch h x v	0.3113 x 0.3113 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D
HDCP	yes
Inputs	USB
Output connector	headphone connector
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 2 W (Stereo)
Included accessories	power cable, D-Sub cable, DVI-D cable, audio cable, USB cable, stand, quick start guide
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, Chinese, RU, JP) and 5 front controls (Power, Menu/ Select, +/ Volume, -/ ECO, Auto)
User controls	luminance (contrast, brightness, ECO, picture mode, ACR), image setup (clock, phase, H. position, V. position, aspect), colour adjust (colour temperature, gamma), OSD setup (H. position, V. position , time out, language), others (reset, signal select, OD, information), volume, auto adjust
Ergonomics	CE, TCO 5.0
Safety	TÜV-Bauart
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	45 W typical; max. 1 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	642 x 438.5 x 210 mm
Weight	6.9 kg
Aspect ratio	16 : 9

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.